

**1. Universal center lathe machine (all geared),
Model: CQ6280C/3000/105mm, Made in China (brand new)**



Actual Picture may vary, Picture with Optional Accessories

Technical Specifications:

- | | |
|---------------------------|-----------------------|
| •Admits between Centers: | 3000 mm |
| •Spindle bore: | 105 mm |
| •Centre Height: | 400 mm |
| •Swing over bed: | <u>800mm</u> |
| •Swing over Gap: | 1000 mm |
| •Swing over slides: | 560 mm |
| •Spindle Speed: | 30- 1400 rpm, |
| •Spindle Speed steps | 12 steps |
| •Main Motor | 7.5 kw |
| •Metric threads | 22 kinds 1-14 mm |
| •Inch threads | 25 kinds 28-2 t.p.i |
| •Module threads: | 18 kinds 0.5-7 πmm |
| •Diametric pitch threads: | 24 kinds 56-4 t.p.i.π |

Complete with Accessories:

- | | |
|---------------------------------------|--|
| •(1nos.) 3-jaw chuck-315mm | (1nos.) 4-jaw chuck-500mm and flange |
| •(1nos.) Steady rest | (1nos.) Follow rest, |
| •(1nos.) Coolant system, | (1nos.) LED work lamp, |
| •(1nos.) 4 Station Vertical Tool post | (1nos.) Drive Plate |
| •(1nos.) Foot brake & Mechanical Stop | (1nos.) Dead Center |
| •(1nos.) Chuck and tool safety cover | (1nos.) Thread chasing dial |
| •(1nos.) Face Plate | (1nos.) instruction manual,Tools & standard electrical |
| • Weight: N.W / G.W | 3200Kg |
| •Dimensions: overall | L 4365 x W 1340 x H 1490mm |