

## **AUTOMECH MACHINE & TOOLS TRADING**


Tel: +971 2 55 40 405, Fax: +971 2 55 40 488, P.O Box: 13060 Mussafah, Abu Dhabi, U.A.E.

Email: machines@automechgroup.com, Web: www.automechmachines.com

## CNC Plasma Cutting Machine (2500x6000 mm) Brand: AMT, Model AMT 2500x6000 Made In Turkey (Brand new)

## UPL 2560 CNC Plasma Cutting Machine (2500x6000 mm)

- XPR 170 Hypertherm Power Source
- Hypertherm EDGE Connect TC
- 19.5" industrial type screen
- Hypertherm operator panel / Hypernet communication system
- Remote connection interface / Phoenix Software
- Core Auto Gas Console
- Sensor THC Torch Height Control
- Hypertherm Pronest Software included with True Hole Technology
- •3 Axis (X,Y,Z)
- 3 pieces AC servo motor and driver / 3 pieces planet type Neugart gear box
- High accuracy linear rails / High accuracy an silent Atlanta Helis rack and pinion
- Ethernet and Network Interfaces, USB Port
- Plasma ignition consol
- Auto Cutting Height Correction Software
- Cutting table with Pneumatic cutting area opening feature
- Air Suction System with Cutting Table
- Moving control panel system





## **AUTOMECH MACHINE & TOOLS TRADING**

Tel: +971 2 55 40 405, Fax: +971 2 55 40 488, P.O Box: 13060 Mussafah, Abu Dhabi, U.A.E.

Email: machines@automechgroup.com, Web: www.automechmachines.com

| CUTTING WIDTH A                         | mm       | 2540                      |
|---|----------|---------------------------|
| TOTAL WIDTH B                           | mm       | 4675                      |
| TOTAL HEIGHT C                          | mm       | 2280                      |
| INTER GAP D                             | mm       | 200                       |
| TORCH DISTANCE E                        | mm       | 0 - 130                   |
| CUTTING LENGTH                          | mm       | 6096                      |
| TABLE HEIGHT                            | mm       | 762                       |
| SPEED                                   | m/min    | 30                        |
| MACHINE AXIS                            | -        | X,Y,Z                     |
| POSITIONING ACCURACY                    | mm       | ± 0,1 DIN 28206           |
| REPITITION ACCURACY                     | mm       | ± 0,05 DIN 28206          |
| CNC CONTROLLER                          |          | Hypertherm EdgeConnect TC |
| CAD/CAM SOFTWARE                        |          | Hypertherm Pronest        |
| PLASMA CUTTING UNIT                     |          | Hypertherm XPR170         |
| TORCH HEIGHT CONTROL                    |          | THC                       |
| MILD STEEL (MAX. CUTTING CAPACITY)      | mm       | 1 - 60                    |
| MILD STEEL (PIERCE)                     | mm       | 1 - 35                    |
| STAINLESS STEEL (MAX. CUTTING CAPACITY) | mm       | 1 - 38                    |
| STAINLESS STEEL (PIERCE)                | mm       | 1 - 22                    |
| ALIMINIUM (MAX. CUTTING CAPACITY)       | mm       | 1 - 38                    |
| ALIMINIUM (PIERCE)                      | mm       | 1 - 25                    |
| CUT ANGLE CLASS                         | ISO 9013 | 2 - 3                     |
| GAS CONSOLE                             |          | CORE (Auto)               |
| ENERGY                                  |          | 400V, 50Hz, 6bar air      |
| WEIGHT                                  | kg       | 7850                      |
| DUST COLLECTOR WEIGHT                   | kg       | 920                       |