

**1. Universal Center lathe machine (all geared) Model: CQ6236K/1000
Made in China (brand new)**



Actual picture may vary

Technical specifications:

- | | |
|--|--------------------|
| • Admits between Centers: | 1000mm |
| • Spindle bore: | 38 mm |
| • Swing over bed: | <u>360 mm</u> |
| • Swing Over Gap: | 506mm |
| • Swing Over Cross slide: | 224 mm |
| • Spindle Nose, internal taper: | D1-4, MT5 |
| • Spindle Speed range: | 70 – 3000rpm |
| • Metric Threads: kinds/range: | 0.4-7 mm |
| • Imperial threads: kinds/range: | 4-60 T.P.I |
| • Longitudinal feeds: | 0.017-0.276 mm/rev |
| • Cross Feeds: | 0.079-1.291 mm/rev |
| • Tailstock quill diameter: | 32 mm |
| • Tailstock Quill travel: | 100 mm |
| • Taper of tailstock quill: | MT 3 |
| • Main motor: | 1.5 kw |
| • Coolant Pump: | 0.08kW |
| • Tail stock sleeve diameter & travel: | 60mm, 120mm |

Complete with

- | | |
|---|---------------------|
| (1nos.) 3-jaw chuck | |
| (1nos.) 4-jaw chuck | (1nos.) Follow rest |
| (1nos.) Steady rest | (1nos.) Light, |
| (1nos.) Coolant pump, | |
| (1nos.) Instruction manual & standard electricals | |